


Trench Field-Stop Technology IGBT

Features

- 1200V, 25A
- $V_{CE(sat)(typ.)}=1.80V @ V_{GE}=15V, I_C=25A$
- Low Switching Losses
- $V_{CE(sat)}$ with Positive Temperature Coefficient
- Pb-free Lead Plating; RoHS Compliant



Applications

- Frequency Converters
- Uninterrupted Power Supply
- Air Conditioning
- Motor Drives

Order codes	V_{CE}	I_C	$V_{CEsat}, T_{vj}=25^\circ C$	T_{vjmax}	Marking	Package
XD025H120CX2S3	1200V	25A	1.80V	175°C	D25H120CX2	TO247

Absolute Maximum Ratings

Symbol	Parameter	Value	Unit
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Continuous Collector Current ($T_c=25^\circ C$)	50	A
	Continuous Collector Current ($T_c=100^\circ C$)	25	A
I_{CM}	Pulsed Collector Current (Note 1)	100	A
I_F	Diode Continuous Forward Current ($T_c=100^\circ C$)	25	A
I_{FM}	Diode Maximum Forward Current (Note 1)	100	A
t_{sc}	Short Circuit Withstand Time	10	us
P_D	Maximum Power Dissipation ($T_c=25^\circ C$)	365	W
	Maximum Power Dissipation ($T_c=100^\circ C$)	183	W
T_J	Operating Junction Temperature Range	-40 to 175	°C
T_{STG}	Storage Temperature Range	-55 to 150	°C

Thermal Data

Symbol	Parameter	Max.	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case for IGBT	0.41	°C/W
$R_{\theta JC}$	Thermal Resistance, Junction to Case for Diode	0.67	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	40	°C/W

IGBT Characteristics ($T_c=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{CES}	Collector-Emitter Breakdown Voltage	$V_{\text{GE}}=0\text{V}$, $I_{\text{C}}=500\mu\text{A}$	1200	---	---	V
I_{CES}	Collector-Emitter Leakage Current	$V_{\text{CE}}=1200\text{V}$, $V_{\text{GE}}=0\text{V}$	---	---	1	mA
I_{GES}	Gate Leakage Current, Forward	$V_{\text{GE}}=20\text{V}$, $V_{\text{CE}}=0\text{V}$	---	---	400	nA
	Gate Leakage Current, Reverse	$V_{\text{GE}}=-20\text{V}$, $V_{\text{CE}}=0\text{V}$	---	---	-400	nA
$V_{\text{GE}(\text{th})}$	Gate Threshold Voltage	$V_{\text{GE}}=V_{\text{CE}}$, $I_{\text{C}}=1.0\text{mA}$	3.5	4.5	5.5	V
$V_{\text{CE}(\text{sat})}$	Collector-Emitter Saturation Voltage	$V_{\text{GE}}=15\text{V}$, $I_{\text{C}}=25\text{A}$	---	1.80	2.20	V
Q_{G}	Total Gate Charge	$V_{\text{CC}}=960\text{V}$ $V_{\text{GE}}=15\text{V}$ $I_{\text{C}}=25\text{A}$	---	122	---	nC
Q_{GE}	Gate-Emitter Charge		---	8.7	---	nC
Q_{GC}	Gate-Collector Charge		---	89	---	nC
$t_{\text{d}(\text{on})}$	Turn-on Delay Time	$V_{\text{CC}}=600\text{V}$ $V_{\text{GE}}=\pm 15\text{V}$ $I_{\text{C}}=25\text{A}$ $R_{\text{G}}=20\Omega$ Inductive Load $T_c=25^\circ\text{C}$	---	34	---	ns
t_r	Turn-on Rise Time		---	42	---	ns
$t_{\text{d}(\text{off})}$	Turn-off Delay Time		---	229	---	ns
t_f	Turn-off Fall Time		---	242	---	ns
E_{on}	Turn-on Switching Loss		---	3.00	---	mJ
E_{off}	Turn-off Switching Loss		---	1.99	---	mJ
E_{ts}	Total Switching Loss		---	4.99	---	mJ
$t_{\text{d}(\text{on})}$	Turn-on Delay Time		---	31	---	ns
t_r	Turn-on Rise Time	$V_{\text{CC}}=600\text{V}$ $V_{\text{GE}}=\pm 15\text{V}$ $I_{\text{C}}=25\text{A}$ $R_{\text{G}}=20\Omega$ Inductive Load $T_c=150^\circ\text{C}$	---	53	---	ns
$t_{\text{d}(\text{off})}$	Turn-off Delay Time		---	296	---	ns
t_f	Turn-off Fall Time		---	398	---	ns
E_{on}	Turn-on Switching Loss		---	3.46	---	mJ
E_{off}	Turn-off Switching Loss		---	2.85	---	mJ
E_{ts}	Total Switching Loss		---	6.31	---	mJ
C_{ies}	Input Capacitance	$V_{\text{CE}}=25\text{V}$ $V_{\text{GE}}=0\text{V}$ $f = 1\text{MHz}$	---	1468	---	pF
C_{oes}	Output Capacitance		---	162	---	pF
C_{res}	Reverse Transfer Capacitance		---	82	---	pF

Diode Characteristics ($T_c=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V_F	Diode Forward Voltage	$I_F=25\text{A}$	---	2.0	2.8	V
t_{rr}	Diode Reverse Recovery Time	$V_{CE}=600\text{V}$ $I_F=25\text{A}$ $dI_F/dt=500\text{A/us}$ $T_c=25^\circ\text{C}$	---	207	---	ns
I_{rr}	Diode Peak Reverse Recovery Current		---	15.6	---	A
Q_{rr}	Diode Reverse Recovery Charge		---	1425	---	nC
t_{rr}	Diode Reverse Recovery Time	$V_{CE}=600\text{V}$ $I_F=25\text{A}$ $dI_F/dt=500\text{A/us}$ $T_c=150^\circ\text{C}$	---	348	---	ns
I_{rr}	Diode Peak Reverse Recovery Current		---	31.1	---	A
Q_{rr}	Diode Reverse Recovery Charge		---	5144	---	nC

Note 1: Repetitive rating, pulse width limited by maximum junction temperature

Typical Characteristics




Fig. 1 Maximum DC Collector Current vs. Case Temperature




Fig. 2 Power Dissipation vs. Case Temperature




Fig. 3 Typical Collector-Emitter Saturation Voltage vs. Junction Temperature at $V_{GE}=15V$




Fig. 4 Safe Operating Area at $T_c=25^\circ C$ and $T_J \leq 175^\circ C$




Fig. 5 Typical IGBT Output Characteristics at $T_J=25^\circ\text{C}$




Fig. 6 Typical Transfer Characteristics at $V_{CE}=20\text{V}$




Fig. 7 Typical Energy Loss vs. I_c at $T_c=25^\circ\text{C}$, $V_{CE}=600\text{V}$, $V_{GE}=\pm 15\text{V}$ and $R_g=20\Omega$







Fig. 8 Typical Switching Time vs. I_c at $T_c=25^\circ\text{C}$, $V_{CE}=600\text{V}$, $V_{GE}=\pm 15\text{V}$ and $R_g=20\Omega$



**Fig. 9 Typical Energy Loss vs. R_g at $T_c=25^\circ\text{C}$,
 $V_{CE}=600\text{V}$, $V_{GE}=15\text{V}$ and $I_C=25\text{A}$**



**Fig. 10 Typical Switching Time vs. R_g at $T_c=25^\circ\text{C}$,
 $V_{CE}=600\text{V}$, $V_{GE}=15\text{V}$ and $I_C=25\text{A}$**



**Fig. 11 Typical Diode I_{rr} vs. dI_F/dt at $V_{CC}=600\text{V}$ and
 $V_F=25\text{A}$**




Fig. 12 Typical Diode Q_{rr} vs. dI_F/dt at $V_{CC}=600\text{V}$ and $V_F=25\text{A}$




Fig. 13 Typical Diode t_{rr} vs. di_F/dt at $V_{cc}=600V$ and $V_F=25A$




Fig. 14 Typical Capacitance vs. V_{ce} at $V_{ge}=0V$ and $f=1MHz$




Fig. 15 Typical Gate Charge vs. V_{ge} at $I_c=25A$





Fig. 16 IGBT Transient Thermal Resistance ($D=t_p/T$)

Package Information

TO-247



COMMON DIMENSIONS (UNITS OF MEASURE = MILLIMETER)			
SYMBOL	MIN	NOM	MAX
A	4.90	5.00	5.10
A1	2.31	2.41	2.51
A2	1.90	2.00	2.10
a	0	—	0.15
a'	0	—	0.15
b	1.16	—	1.26
b1	1.15	1.2	1.22
b2	1.96	—	2.06
b3	1.95	2.00	2.02
b4	2.96	—	3.06
b5	2.96	3.00	3.02
b6	---	—	2.25
b7	---	—	3.25
c	0.59	—	0.66
c1	0.58	0.60	0.62
D	20.90	21.00	21.10
D1	16.25	16.55	16.85
D2	1.05	1.17	1.35
E	15.70	15.80	15.90
E1	13.10	13.30	13.50
E2	4.40	4.50	4.60
E3	1.50	1.60	1.70
e	5.436 BSC		
L	19.80	19.92	20.10
L1	—	—	4.30
M	0.35	—	0.95
P	3.40	3.50	3.60
P1	7.00	—	7.40
P2	2.40	2.50	2.60
Q	5.60	—	6.00
S	6.05	6.15	6.25
T	9.80	—	10.20
U	6.00	—	6.40

NOTES:

ALL DIMENSIONS REFER TO JEDEC STANDARD TO-247 AND

DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.

EJECTION MARK DEPTH $0.10^{+0.15}_{-0.10}$